



1 HOUR
Fire Rating




NONE
Airtight Rating



PICTURE
Frame



NONE
Acoustic Rating



Description

This panel is designed to fit into a structural membrane of a joint-less plasterboard wall & ceiling system. It is manufactured with a 25mm wide picture frame.. The panel has a Metal faced door.The panels door leaf is locked in place via a 3 Point Locking System as standard other lock options are available upon request. The Panel is Powder Coated RAL 9010 30% Gloss. Other colours available upon request.

Tests

The Panel is 1 Hour Fire Rated up to 2000x900mm in a wall application tested in accordance with BS 476: Part 22: 1987.

The Panel is acoustic rated to 40dB tested in accordance with BS EN ISO 140-3:1995. Single number quantities were calculated in accordance with BS EN ISO 717-1:1997.

The panel is Not Air pressure tested

Composition & Manufacture

The PAL02-060-MD-PF-3WL-40A is manufactured from Zintec Steel with a 0.9mm thick Door and a 1.2mm Frame. The panels door leaf is hinged by a Full Piano Hinge.

Key Features:

Intumescent Seals **YES** Draught Seals **YES** Smoke Seals **NO** Air Seals **NO** Acoustic Seals **YES**

Fitting

Make sure the structural opening is at least 7mm larger than the panel size, back of frame size. E.G a 600x600mm panel size requires a 607x607mm hole size. Remove the door from the frame and place the frame into the set hole. Fix through the appropriate fixing holes within the fold up fixing tabs ensuring the frame is pushed up against the structural opening surround. Check the frame is square by measuring corner to corner. Refit door and lock in place; the door and frame should be flush. Independent bracing or support may be required to take the weight of the Access Panel. Apply fire mastic on both faces of the frame, nominally 5mm wide sealing to the supporting construction.